

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
18 August 2005 (18.08.2005)

PCT

(10) International Publication Number
WO 2005/076536 A1

(51) International Patent Classification⁷: **H04L 12/46**,
12/40, 29/06

(74) Agents: KAWAMIYA, Osamu et al.; AOYAMA & PART-
NERS, IMP Building, 3-7, Shiromi 1-chome, Chuo-ku, Os-
aka-shi, Osaka 5400001 (JP).

(21) International Application Number:
PCT/JP2005/002086

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(22) International Filing Date: 2 February 2005 (02.02.2005)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
2004-027746 4 February 2004 (04.02.2004) JP

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

(71) Applicant (for all designated States except US): MAT-
SUSHITA ELECTRIC INDUSTRIAL CO., LTD.
[JP/JP]; 1006, Oaza Kadoma, Kadoma-shi, Osaka
5718501 (JP).


(72) Inventors; and

(75) Inventors/Applicants (for US only): LIM, Wei Lih.
TAN, Pek Yew. APICHAICHALERMWONGSE,
Chalermphol. ANDO, Kazuhiro. HARADA, Yasuo.

Published:
— with international search report

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR GENERATING PACKET FRAMES FOR CARRYING DATA



(57) Abstract: A conventional packet frame includes a MAC header, one MAC service data unit (MSDU) and a frame FCS. This frame is repeated to send a plurality of MSDUs. A proposed packet frame includes a MAC header, a plurality of MSDUs and a frame FCS. A unique bit pattern is provided in the MAC header to distinguish the proposed packet frame from the conventional packet frame. Thus, the total data stream can be shortened.



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.